Unshielded M12 Connector Male With Molded Cable Straight PVC Assembly 4 Pin

Basic Information

• Place of Origin: Guangdong, China

Brand Name: KRONZCertification: CE

Model Number: M1204M-3/P00R

Minimum Order Quantity: 50 pieces
 Price: Negotiable
 Packaging Details: Polybag packing
 Delivery Time: 5-8 working days

Payment Terms: T/T, Western Union, MoneyGram

• Supply Ability: 100000 pieces per month



Product Specification

Product Name: M12 Field-wireable Assembly Connector

Connection Method: Screw ConnectionMaterial: Brass,nickle-plated

Degree Of Protection: IP67Pollution Degree: 3

• Insulation Resistance: $\geq 100 M\Omega$ • Contact Resistance: $\leq 5 m\Omega$ • Ambient Temperature: $-25^{+}85$

• Highlight: Unshielded M12 Connector Male,

M12 Connector Male 4 Pin,

Straight PVC Assembly M12 Connector




Product Description

M12 Connectors with Molded Cable Unshielded Male Straight PVC Assembly 4 Pin

Product Description

The M12 connector are available with different pin configurations (2 to 12 pins) to support a range of applications, including power supply, signal transmission, and data communication.





Technical Data

Standard	IEC 61076-2-101				
Contact nut material	Brass, nickle-plated				
Contact surface material	Brass, gold-plated				
Contact carrier material	PA, black				
Housing material	TPU, black				
Seal material	FPM/FKM				
Insulation resistance	≥100MΩ				
Contact resistance	≤5mΩ				
Pollution degree	3				
Ambient temperature	-25~+85				
Mating cycles	>100				
Degree of protection	IP67				

PIN	Connec tion method	Coding	Rated current	Voltage	Wire gauge	Cable outlet	Length	Model No.
3 2 4 1	1=BN 2=WH 3=BU 4=BK	А	4A	250V	4×0.34 (4×22AWG) PVC, black	Straigh t	3M	M1204M-3/P00R

KRONZ Kronz (guangzhou) Electronics Co., Ltd.



+8618924160375



sales02@kronz.cn



© connector-industrial.com

6th Floor, B602 Building, No.10, Rong Jing 2nd Road, Yu Shan Guo Ji, Yong Ning Street, Zeng Cheng District, Guangzhou, P.R.China