



U18 Ultrasonic Sensor NPN Switching Output 30-300mm 10-30VDC M12 Connector

Our Product Introduction

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: KRONZ
- Certification: CE
- Model Number: U18-D300N(P)1T-R00A
- Minimum Order Quantity: 5 pieces
- Price: Negotiable
- Packaging Details: Polybag packing
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 100000 pieces per month



Product Specification

- Features: Easy To Instal
- Series: U18 Serial
- Description: U18 Ultrasonic Sensors, Ultrasonic Sensor
- Type: Ultrasonic Sensor
- Detection Range: 50-500mm
- Input Type: Teach-in And Synchronization
- Meterial: Copper Nikel-plated,plastic Fitting,glass Epoxy Resin
- Connection Type: 5pin, M12 Connector
- Highlight: **U18 Ultrasonic Sensor NPN,
M12 Connector Ultrasonic Sensor NPN,
Ultrasonic Sensor NPN 10VDC**



Product Description

U18 Ultrasonic Sensor NPN Switching Output 30-300mm 10-30VDC M12 Connector

Main Feature:

- ▶ M18 installation threaded sleeve
- ▶ Easy to instal

Basic Feature:

- ▶ 1 pc npn or pnp switching output
- ▶ Support digital RS485, modbus-rut standard protocol communication
- ▶ Analog voltage output 0-10V or analog current output 4-20 mA
- ▶ Implementing detection distance learning function through gray lines
- ▶ Temperature compensation
- ▶ Standard operating voltage DC 10-30V

Model	U18-D300N(P)1T-R00A
Dection range	30-300mm
Blind zone	0-30mm
Resolution	0.1mm
Repeatability	±0.15%F.S.
Accuracy	±1%(built-in temperature drift compensation)
Response time	22ms
Switching hysteresis	2mm
Switching frequency	45Hz
Initialization time	500ms
Supply voltage	10-30V DC,reverse-polarity protection
Red LED	no object detected:Lights up, teaching-in when no object detected:Flashes
Green LED	object detected:Lights up, teaching-in when object detected:Flashes
Overcurrent protection	200mA,Red LED and Green LED flashing at the same time
Load impedance	I/ 300 Ohm,U/ 1k Ohm
No-load current	≤30mA
Input type	teach-in and synchronization
Material	Copper nikel-plated,plastic fittings,glass epoxy resin.
Enclosure rating	IP67
Connection type	5pin, M12 connector
Ambient temperature	-25 ~+70 (248~343K)
Storage temperature	-40 ~+85 (233~358K)
Weight	35g
Output type	N1: 1 npn switching output NO/NC P1: 1 pnp switching output NO/NC
Dimensional drawing	

KRONZ Kronz (guangzhou) Electronics Co., Ltd.



+8618924160375



sales02@kronz.cn



connector-industrial.com

6th Floor, B602 Building, No.10, Rong Jing 2nd Road, Yu Shan Guo Ji, Yong Ning Street, Zeng Cheng District,

