

IEC 61076-2-104 M8 Connector 4 Pin With Cable Straight Female A Code PVC Shielded

Basic Information

• Place of Origin: Guangdong, China

Brand Name: KRONZCertification: CE

Model Number: M0804F-2/SOOR

Minimum Order Quantity: 50 pieces
 Price: Negotiable
 Packaging Details: Polybag packing
 Delivery Time: 5-8 working days

Payment Terms: T/T, Western Union, MoneyGram

• Supply Ability: 100000 pieces per month



Product Specification

Product Name: M8 Pre-Assembled Cable Connector

Contact Nut Material: Brass, Nickle-plated
 Contact Surface Material: Brass, Gold-plated

• Contact Carrier Material: PA, Black
• Housing Material: TPU, Black
• Insulation Resistance: $\geq 100 M\Omega$ • Contact Resistance: $\leq 5 m\Omega$ • Pollution Degree: 3

• Highlight: IEC 61076-2-104 M8 Connector 4 Pin,

Female M8 Connector 4 Pin, PVC Shielded M8 Female Connector




Product Description

IEC 61076-2-104 M8 Connector 4 Pin with Cable Straight Female A Code PVC Shieled

Product Description

With various pin configurations and coding options, M8 connectors can support different types of connections, including power, signal, and data. This versatility makes them suitable for a wide range of applications.



Technical Data

| Standard | IEC 61076-2-104 | | | |
|--------------------------|----------------------|--|--|--|
| 0.101.10101.10 | | | | |
| Contact nut material | Brass, nickle-plated | | | |
| Contact surface material | Brass, gold-plated | | | |
| Contact carrier material | PA, black | | | |
| Housing material | TPU, black | | | |
| Seal material | FPM/FKM | | | |
| Insulation resistance | ≥100MΩ | | | |
| Contact resistance | ≤5mΩ | | | |
| Pollution degree | 3 | | | |
| Ambient temperature | -25~+85 | | | |
| Mating cycles | >100 | | | |
| Degree of protection | IP67 | | | |

| Pin | Wire | Codin | Rated | Voltage | Wire gauge | Cable | Length | Model No. | | |
|----------------------|-------|-------------|---------|----------------------------|------------|---------|----------------------------|---------------|--------|-----------|
| assignment | color | g | current | Vollage | Vollage | t | Rated Voltage Wire gauge o | outlet | Lengun | Model No. |
| | 1-RN | 1=BN =WH | | | 4x0.25 | Straigh | 2M | M0804M-2/SOOR | | |
| 2=WH 3=BU 4=BK | | | l l | | (4x24AWG) | | 5M | M0804M-5/SOOR | | |
| | A | 3A | UU V | PVC, shielded,bla ck | + 1 | | M0804M-10/SOOR | | | |

KRONZ Kronz (guangzhou) Electronics Co., Ltd.



+8618924160375



sales02@kronz.cn



connector-industrial.com

6th Floor, B602 Building, No.10, Rong Jing 2nd Road, Yu Shan Guo Ji, Yong Ning Street, Zeng Cheng District, Guangzhou, P.R.China