



## 5 Pin M12 Connector Industrial Ultrasonic Sensor 30-300mm Detection Range

Our Product Introduction

### Basic Information

- Place of Origin: Guangdong, China
- Brand Name: KRONZ
- Certification: CE
- Model Number: U18-D300UIT-R00A
- Minimum Order Quantity: 10 pieces
- Price: Negotiable
- Packaging Details: Polybag packing
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 100000 pieces per month



### Product Specification

- Detection Range: 30-300mm
- Blind Zone: 0-30mm
- Resolution: 0.1mm
- Response Time: 22ms
- No-load Current:  $\leq 30\text{mA}$
- Supply Voltage: 10-30V DC
- Enclosure Rating: IP67
- Connection Type: 5pin, M12 Connector
- Highlight: **M12 Connector Industrial Ultrasonic Sensor,  
5 Pin Industrial Ultrasonic Sensor,  
5 Pin M12 Connector Ultrasonic Sensor**



for more products please visit us on [connector-industrial.com](http://connector-industrial.com)

## Product Description

### Ultrasonic Sensor Analog Current Voltage Output 30-300mm 5 Pin M12 Connector

#### Product Description

Main Feature:

- M18 installation threaded sleeve
- Easy to instal

Basic Feature:

- 1 pc npn or pnp switching output
- Support digital RS485, modbus-rut standard protocol communication
- Analog voltage output 0-10V or analog current output 4-20 mA
- Implementing detection distance learning function through gray lines
- Temperature compensation
- Standard operating voltage DC 10-30V

Model	U18-D300UIT-R00A
Dection range	30-300mm
Blind zone	0-30mm
Resolution	0.1mm
Repeatability	±0.15%F.S.
Accuracy	±1%(built-in temperature drift compensation)
Response time	22ms
Initialization time	< 500ms
Supply voltage	10-30V DC,reverse-polarity protection
Red LED	no object detected:Lights up, teaching-in when no object detected:Flashes
Green LED	object detected:Lights up, teaching-in when object detected:Flashes
Overcurrent protection	200mA,Red LED and Green LED flashing at the same time
Load impedance	I/ 300 Ohm,U/ 1k Ohm
No-load current	≤30mA
Input type	Teach-in and synchronization
Material	Copper nikel-plated,plastic fittings,glass epoxy resin.
Enclosure rating	IP67
Connection type	5pin, M12 connector
Ambient temperature	-25 ~+70 (248~343K)
Storage temperature	-40 ~+85 (233~358K)
Weight	35g
Output type	UI: 1 analog voltage output 0-10V + 1 analog current output 4-20mA, up/down
Dimensional drawing	

**KRONZ** Kronz (guangzhou) Electronics Co., Ltd.



+8618924160375



sales02@kronz.cn



[connector-industrial.com](http://connector-industrial.com)

6th Floor, B602 Building, No.10, Rong Jing 2nd Road, Yu Shan Guo Ji, Yong Ning Street, Zeng Cheng District, Guangzhou, P.R.China

