



IP67 Industrial Ultrasonic Sensors U12 Analog Output M12 Connector

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: KRONZ
- Certification: CE
- Model Number: U12-D120IT-R00A
- Minimum Order Quantity: 5 pieces
- Price: Negotiable
- Packaging Details: Polybag packing
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 100000 pieces per month



Product Specification

- Description: Ultrasonic Sensors U12
- Detection Range: 20-120mm
- Output: Analog Current Output 4-20mA
- LED Color: Green, Red
- Blind Zone: 0-20mm
- Resolution: 0.1mm
- No-load Current: $\leq 30\text{mA}$
- Supply Voltage: 10-30VDC
- Highlight: Industrial Ultrasonic Sensors U12, M12 Connector Industrial Ultrasonic Sensors, IP67 Industrial Ultrasonic Sensors



Product Description

Ultrasonic Sensor U12 IP67 20-120mm Detection Range Analog Output M12 Connectors

Product Description

Main Feature:


- M12 installation threaded sleeve, the shortest full length is only 57mm
- Small blind zone, small sound cone, suitable for close-range fine detection

Basic Feature:

- 1 pc npn or pnp switching output
- Realize detection distance learning function through white lines
- Temperature compensation
- Standard operating voltage DC 10-30V

| | |
|------------------------|---|
| Model | U12-D120IT-R00A |
| Detection range | 20-120mm |
| Blind zone | 0-20mm |
| Resolution | 0.1mm |
| Repeatability | ±0.15%F.S. |
| Accuracy | ±1%(built-in temperature drift compensation) |
| Response time | 18ms |
| Initialization time | 500ms |
| Supply voltage | 10-30V DC, reverse-polarity protection |
| Red LED | no object detected:Lights up, teaching-in when no object detected:Flashes |
| Green LED | object detected:Lights up, teaching-in when object detected:Flashes |
| Overcurrent protection | 200mA, Red LED and Green LED flashing at the same time |
| Load impedance | I/ 300 Ohm, U/ 1k Ohm |
| No-load current | ≤30mA |
| Input type | Teach-in and synchronization |
| Material | Copper nickel-plated, plastic fittings, glass epoxy resin. |
| Enclosure rating | IP67 |
| Connection type | 4pin, M12 connector |
| Ambient temperature | -25 ~+70 (248~343K) |
| Storage temperature | -40 ~+85 (233~358K) |
| Weight | 16g |
| Output type | I: 1 analog current output 4-20mA |

Dimensional drawing



KRONZ Kronz (guangzhou) Electronics Co., Ltd.



+8618924160375



sales02@kronz.cn



connector-industrial.com

6th Floor, B602 Building, No.10, Rong Jing 2nd Road, Yu Shan Guo Ji, Yong Ning Street, Zeng Cheng District, Guangzhou, P.R.China