



## 7/8"-16UN Circular 7/8" Connector With Pre Molded Cable IP67 4 Pin Female Straight

Our Product Introduction

### Basic Information

- Place of Origin: Guangdong, China
- Brand Name: KRONZ
- Certification: CE
- Model Number: M7804F-2/P00R
- Minimum Order Quantity: 50 pieces
- Price: Negotiable
- Packaging Details: Polybag packing
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 100000 pieces per month



### Product Specification

- Product Name: 7/8"-16UN Connector
- Wire Gauge: 4×0.15 (4×16AWG) PVC, Black
- Cable Length: 2M/5M/10M/Customized
- Voltage: 600V
- Rated Current: 8A
- Wire Color: 1=BK 2=BU 3=BN 4=WH
- Highlight: **Circular 7/8" Connector,  
IP67 Circular 7/8" Connector,  
7/8"-16UN 4 Pin Female Connector**



for more products please visit us on [connector-industrial.com](http://connector-industrial.com)

## Product Description


### 7/8"-16UN Circular Connector with Pre-molded Cable IP67 4 Pin Female Straight

#### Product Description

Between the equipment in the automated production line, the 7/8" field connector helps to achieve quick connection and disassembly, facilitating equipment maintenance and replacement. When equipment in a certain production link fails, this connector can quickly disconnect. Open the connection, remove the faulty equipment and replace it with spare equipment, which greatly reduces the downtime of the production line and improves production efficiency. For example, in the automobile manufacturing assembly line, if there is a problem with the engine assembly equipment, the 7/8" field connector can be used. Quickly replace equipment to ensure continuous operation of the production line.

#### Technical Data

Thread type	7/8"-16UN
Contact nut material	Zinc alloy, nickel-plated
Contact surface material	Brass, gold-plated
Contact carrier material	PA, black
Housing material	PBT/PA, black
Seal material	FPM/FKM
Insulation resistance	$\geq 100M\Omega$
Contact resistance	$\leq 5m\Omega$
Pollution degree	3
Ambient temperature	-25~+85
Mating cycles	>100
Degree of protection	IP67

Pin assignment	Wire color	Coding	Rated current	Voltage	Wire gauge	Cable outlet	Length	Model No.
	1=BK 2=BU 3=BN 4=WH	A	8A	600V	4×0.15 (4×16AWG) PVC, black	Straight	2M	M7804F-2/P00R
	5M						M7804F-5/P00R	
	10M						M7804F-10/P00R	

\*Cable length: 2/5/10m, other cable lengths are available on request! Freely selectable cable material (P00R: black, PVC, P01R: black, PUR)

## KRONZ Kronz (guangzhou) Electronics Co., Ltd.



+8618924160375



[sales02@kronz.cn](mailto:sales02@kronz.cn)



[connector-industrial.com](http://connector-industrial.com)

6th Floor, B602 Building, No.10, Rong Jing 2nd Road, Yu Shan Guo Ji, Yong Ning Street, Zeng Cheng District, Guangzhou, P.R.China