



20-60°C Operating Temperature 30±4mm Sensing Distance Photoelectric Sensor for Industrial Applications

Our Product Introduction

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: KRONZ
- Certification: CE
- Model Number: KD50-L30N
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: Polybag packing
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 10000 pieces per month



Product Specification

- Operating Temperature: -10~45°C
- Vibration Resistance: 10~55Hz, Double Amplitude 1.5mm, X、Y、Z Directions, 2 Hour For Each
- Operating Humidity: 35~85%RH(no Condensation Or Icing)
- Ambient Illuminance: Sunlight: ≤10000lux, Lamp: ≤3000lux
- Wavelength: 655nm
- Storage Humidity: 35~95%RH(no Condensation Or Icing)
- Weight: Cable Type: 65g
- Housing Material: Housing: PBT, Lens: PMMA
- Highlight: **Industrial Photoelectric Sensor, 34mm Distance Photoelectric Sensor**



Product Description:

The Photoelectric Sensors product is a versatile and reliable solution designed for a wide range of applications, including machine guarding and automation systems. The CMOS sensor enables **fast processing**, **high resolution**, and **stable performance** even for challenging surfaces (e.g., glossy, dark, or rough textures).

KRONZ





Cable Type	2CH+Analog Current	KD50-L30N
Output Signal		Switching output: NPN (-N)
Detection Range		26.3±2mm
Full Scale (F.S.)		4mm
Spot Size	Near Range	0.15 x 0.15mm
Linearity Accuracy		±0.2%F.S.
Repeatability		1µm
Response Time	High-speed Mode	max.5ms: sampling average x 1 (1ms) + sensitivity switch time (max.4ms)
	Standard Mode	max.12.5ms: sampling average x 16 (8.5ms) + sensitivity switch time (max.4ms)
IP Rating		IP67

KD50 Series

CMOS Laser Displacement Sensor

- Built-in analog output and 2 digital outputs, operable without a controller connection.
- High-precision photosensitivity calibration auto-optimizes received light intensity.
- Digital subpixel processing technology delivers over twice the linear accuracy of conventional displacement sensors.
- Remote input (MF line) enables functions including: laser emission off, external teach-in, output hold, and single-pulse input.



Technical Parameters

Diffuse Reflection

Cable Type	2CH	KD50-30N(P)	KD50-50N(P)	KD50-85N(P)	KD50-120N(P)	KD50-250N(P)
	2CH+Analog Current	KD50-30N(P)I	KD50-50N(P)I	KD50-85N(P)I	KD50-120N(P)I	KD50-250N(P)I
	2CH+Analog Voltage	KD50-30N(P)U	KD50-50N(P)U	KD50-85N(P)U	KD50-120N(P)U	KD50-250N(P)U
Plug-in Type	1CH+RS422	KD50-30N(P)/R2	KD50-50N(P)/R2	KD50-85N(P)/R2	KD50-120N(P)/R2	KD50-250N(P)/R2
	2CH	KD50-30N(P)-A8	KD50-50N(P)-A8	KD50-85N(P)-A8	KD50-120N(P)-A8	KD50-250N(P)-A8
	2CH+Analog Current	KD50-30N(P)I-A8	KD50-50N(P)I-A8	KD50-85N(P)I-A8	KD50-120N(P)I-A8	KD50-250N(P)I-A8
Plug-in Type	2CH+Analog Voltage	KD50-30N(P)U-A8	KD50-50N(P)U-A8	KD50-85N(P)U-A8	KD50-120N(P)U-A8	KD50-250N(P)U-A8
	1CH+RS422	KD50-30N(P)/R2-A8	KD50-50N(P)/R2-A8	KD50-85N(P)/R2-A8	KD50-120N(P)/R2-A8	KD50-250N(P)/R2-A8
	2CH	KD50-30N(P)-A8	KD50-50N(P)-A8	KD50-85N(P)-A8	KD50-120N(P)-A8	KD50-250N(P)-A8
Output Signal		Switching output: NPN (-N), PNP (-P); Analog output: current 4-20mA, voltage 0-10V; Communication output: RS-422				
Detection Range		30±4mm	50±10mm	85±20mm	120±60mm	250±150mm
Full Scale (F.S.)		8mm	20mm	40mm	120mm	300mm
Light Source		Red Laser diode (wavelength 655nm)				
IEC/JIS Rating (FDA Rating)		Class 2(Class II)				
Sampling Period		500 (250mm: 750) /1000/1500/2000μs ;factory setting: 500μs (250mm: 750μs)				
Spot Size (max.)	Near Range	0.15x0.15mm	0.6x1.2mm	0.9x1.5mm	1.2x1.8mm	1.5x2.5mm
	Center Range	0.1x0.1mm	0.5x1.0mm	0.75x1.25mm	1.0x1.5mm	1.75x3.5mm
	Far Range	0.15x0.15mm	0.4x0.9mm	0.6x1.0mm	0.5x0.8mm	2.0x4.5mm
Linearity Accuracy		±0.1%F.S.				
Repeatability	High speed Mode	4μm	8μm	15μm	45μm	100μm
	Other Mode	2μm	5μm	10μm	30μm	75μm
Temperature Drift		±0.08%F.S./°C				
Response Time	High-speed Mode	max.5ms: sampling average x 1 (1ms) + sensitivity switch time (max.4ms)				1.5ms+6ms max. (sampling average: 1)
	Standard Mode	max.12.5ms: sample average x 16 (8.5ms) + sensitivity switch time (max.4ms)				13ms+6ms max. (sampling average: 16)
	High-resolution Mode	max.36.5ms: sampling average x 64 (32.5ms) + sensitivity switch time (max.4ms)				49ms+6ms max. (sampling average: 64)
	Sensitivity Switch Time	4ms max.				
Indicator		Distance indicator: 7 bar LED display; output indicator: ON state: orange Q1/Q2 indicator (orange) light				
IP Rating		IP67				
Operating Temp./Humidity		-10~45° C/35~85%RH(no condensation or icing)				
Storage Temp./Humidity		-20~60° C/35~95%RH(no condensation or icing)				
Ambient Illuminance		Sunlight: ≤ 10000lux, lamp: ≤ 3000lux				
Vibration Resistance		10~55Hz, double amplitude 1.5mm,X、Y、Z directions, 2 hour for each				
Shock Resistance		50G (500m/s²)				
Housing Material		Housing: PBT Lens: PMMA				
Weight		Cable type: 65g; Plug-in type: 70g				

Output

分类	2CH (Switching Output)	2CH+Analog Current Output	2CH+Analog Voltage Output	1CH+RS422
Power Supply Voltage	12-24V DC (-5%,+10%)		18-24V DC (-5%, +10%)	12-24V DC (-5%, +10%)
Current Consumption	max.55mA(24VDC)	max.85mA(24VDC)	max.55mA(24VDC)	
Switching Q1 Output	NPN or PNP open collector, $\leq 100\text{mA}/30\text{V DC}$, residual voltage $\leq 1.8\text{V}$			/
Switching Q2 Output	NPN or PNP open collector, $\leq 100\text{mA}/30\text{V DC}$, residual voltage $\leq 1.8\text{V}$			/
Analog Output	/	4-20mA	0-10V	/
Communication	/			RS422
Cable Type	$\Phi 5\text{mm}$ 5-pin 2m cable		$\Phi 5\text{mm}$ 6-pin 2m cable	$\Phi 5\text{mm}$ 8-pin 2m cable
Plug-in Type	M12 8-pin			

Retro-reflective

Cable Type	2CH+Analog Current	KD50-L30N(P)I	KD50-L50N(P)I	KD50-L85N(P)I
	2CH+Analog Voltage	KD50-L30N(P)U	KD50-L50N(P)U	KD50-L85N(P)U
Plug-in Type	1CH+RS422	KD50-L30N(P)/R2	KD50-L50N(P)/R2	KD50-L85N(P)/R2
	2CH+Analog Current	KD50-L30N(P)I-A8	KD50-L50N(P)I-A8	KD50-L85N(P)I-A8
Plug-in Type	2CH+Analog Voltage	KD50-L30N(P)U-A8	KD50-L50N(P)U-A8	KD50-L85N(P)U-A8
	1CH+RS422	KD50-L30N(P)/R2-A8	KD50-L50N(P)/R2-A8	KD50-L85N(P)/R2-A8
Output Signal		Switching output: NPN (-N), PNP (-P)		
Detection Range		26.3±2mm	47.3±5mm	82.9±10mm
Full Scale (F.S.)		4mm	10mm	20mm
Light Source		Red Laser diode (wavelength 655nm)		
激光功率		390μW max.		
IEC/JIS Rating		Class I		
FDA Rating		Class II		
Sampling Period		500 (250mm: 750) / 1000/1500/2000μs; factory setting: 500μs (250mm: 750μs)		
Spot Size	Near Range	0.15 x 0.15mm		
	Center Range	0.1 x 0.1mm		
	Far Range	0.15 x 0.15 mm		
Linearity Accuracy		±0.2%F.S.		
Repeatability		1μm	2.5μm	5μm
Temperature Drift		±0.08%F.S./°C		
Response Time	High-speed Mode	max.5ms: sampling average x 1 (1ms) + sensitivity switch time (max.4ms)		
	Standard Mode	max.12.5ms: sampling average x 16 (8.5ms) + sensitivity switch time (max.4ms)		
	High-resolution Mode	max.36.5ms: sampling average x 64 (32.5ms) + sensitivity switch time (max.4ms)		
	Sensitivity Switch time	4ms max.		
Indicator				
IP Rating		IP67		
Operating Temp./Humidity		-10~45° C/35~85%RH (no condensation or icing)		
Storage Temp./Humidity		-20~60° C/35~95%RH (no condensation or icing)		
Ambient Illuminance		Lamp: $\leq 3000\text{lux}$		
Vibration Resistance		10~55Hz, double amplitude 1.5mm,X, Y, Z directions, 2 hour for each		
Shock Resistance		50G (500m/s ²) X, Y, Z 3 times for each		
Housing Material		Housing: PBT Lens: PMMA		
Weight		Cable type: 65g; Plug-in type: 70g		

Applications:

KRONZ Photoelectric Sensors are versatile sensors suitable for a wide range of product application occasions and scenarios due to their high-quality features and specifications. These sensors, originating from Guangdong, China, come with CE certification, ensuring their reliability and performance.

Height or Thickness Control: Ensuring consistent material thickness in processes like film extrusion or sheet metal production.

Positioning and Alignment: Used in robotic systems to precisely align tools or components.

KRONZ

ABOUT US

KRONZ is a manufacturing enterprise located in Zengcheng District, Guangzhou City. We focus on providing customers with high-efficiency industrial automation solutions and related industrial products. After many years of innovation and development, KRONZ has complete product processing equipment and a professional team who are proficient in various automation technologies.

In order to improve the quality of products and production efficiency, we continue to introduce advanced production equipment and technology, strengthen investment in research and development. At present, our main products include Industrial Connectors, Inductive Sensors, Capacitive Sensors, Photoelectric Sensors, Ultrasonic Sensors, Industrial power supplies, Industrial fieldbus, RFID recognition systems, Industrial Ethernet Switches

We not only produce the orders of standard products, but also have ability to make customize production based on customer design drawings or samples.

Adhering to the principle of mutual benefit, we provide our customers with competitive prices , and perfect after-sales service. Kronz's products have been sold in multiple countries, have won the trust and praise of customers. KRONZ expect to collaborate with you.

OUR FACTORY



[illegible]

Logistics and Payment



1. Samples and small orders can be shipped with fast shipment method, by air and by express. Bulk order will ship by sea, by air, by train, by truck etc.

2. We also can send the goods to your agent warehouse.

3. If you need any more shipping method, please feel free to contact with us.





Note:

Due to the wide range of our products, we cannot list all product pictures and corresponding product parameters. If you have other needs, please communicate with me. We can provide supplementary information and technical support.
We Are Happy to Serve You.



KRONZ Kronz (guangzhou) Electronics Co., Ltd.



+8618924160375



sales02@kronz.cn



connector-industrial.com

6th Floor, B602 Building, No.10, Rong Jing 2nd Road, Yu Shan Guo Ji, Yong Ning Street, Zeng Cheng District,
Guangzhou, P.R.China