



M12 Male Field Wirable Connector with 5 Pin A-CODE Keying and IP67 Protection for Industrial Automation

Our Product Introduction

for more products please visit us on connector-industrial.com

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: KRONZ
- Certification: CE
- Model Number: H1205M-11
- Minimum Order Quantity: 10 pieces
- Price: Negotiable
- Packaging Details: Paper box packing
- Delivery Time: 5-8 working days
- Payment Terms: T/T,D/P
- Supply Ability: 100000 pieces per month

KRONZ

Product Specification

- Standard: IEC 61076-2-101
- Pin Count: 5 Pin
- Coding: A-CODE
- Rated Current: 4 A
- Rated Voltage: 60 V
- Cable Outlet Diameter: 7-9 Mm (PG11)
- Highlight: **5 Pin M12 Male Connector,
A-CODE Keying M12 Field Wirable Connector,
IP67 Protection M12 Industrial Connector**

Product Description

M12 Male Field Wirable Assembly, Straight

H1205M-11 is a field-wirable M12 male straight connector designed for industrial automation and fieldbus applications, including sensors, actuators, I/O modules, and control cabinet wiring.

The straight outlet structure enables vertical installation in confined spaces. The 5-pin male interface with A-CODE keying effectively prevents mis-mating. Brass gold-plated contacts combined with screw clamp terminals allow reliable wiring on-site without special crimping tools, significantly reducing installation and maintenance costs.

The housing body is made of high-strength PA/PBT engineering plastic, the coupling nut is zinc-alloy nickel-plated, and seals are made of FPM/FKM material. The overall design achieves IP67 protection and remains stable in dusty, oily, and briefly submerged environments. The product complies with IEC 61076-2-101 and supports more than 100 mating cycles, making it suitable for machine tools, robots, logistics conveyors, and new energy equipment.

Key Specifications

Parameter	Value
Ordering Model	H1205M-11
Type	Male / Straight
Pin Count	5 Pin
Coding	A-CODE
Connection method	Solder connection
Cable Gland	PG11 (7-9 mm)
Rated Current	4 A
Rated Voltage	60 V
Protection Class	IP67
Operating Temperature	-25 ~ +85

Technical Parameters

Parameter	Value
Standard	IEC 61076-2-101
Pin Count	5 Pin
Coding	A-CODE
Rated Current	4 A
Rated Voltage	60 V
Contact Resistance	≤ 5 mΩ
Insulation Resistance	≥ 100 MΩ
Connection method	Solder connection (Field Wirable)
Cable Outlet Diameter	7-9 mm (PG11)
Protection Class	IP67
Operating Temperature	-25 ~ +85
Pollution Degree	3
Mechanical Life	>100 Mating Cycles

Coupling Nut Material	Zinc Alloy, Nickel-plated
Contact Material	Brass, Gold-plated
Insert Material	PA, Black
Clamp Body Material	PBT/PA, Black
Seal Material	FPM / FKM

Note: The above are typical parameters. Please evaluate the actual application in combination with cable specifications, installation method, and environmental conditions.

Product Features

- 5-pin industrial male interface with A-CODE keying prevents mis-mating and improves system safety.
- IP67 industrial protection blocks dust and water jets, suitable for outdoor, machine tool, and washdown environments.
- Field screw termination requires no crimping dies; a common screwdriver completes wiring for fast installation and maintenance.
- PG11 cable gland fits 7-9 mm outer diameter cables and provides reliable strain relief and sealing.
- Gold-plated brass contacts deliver contact resistance as low as $\leq 5\text{ m}\Omega$, resisting oxidation and ensuring long-term stable conduction.
- Wide operating temperature range from -25 to $+85$ covers most industrial high/low temperature challenges.

Applications

- H1205M-11 is suitable for a variety of industrial scenarios requiring reliable field connection of sensors and actuators to control systems.
- Industrial Automation: PLC, I/O modules, sensors, and actuators field wiring.
- Machine Vision & Inspection: Multi-core signal transmission for cameras and lighting controllers.
- Robotics & Conveyors: Resistant to vibration and oil, meeting mobile equipment connection requirements.





Frequently Asked Questions

Q: How many conductors does H1205M-11 support?

A: H1205M-11 is a 5-pin male straight field-wirable connector with A-CODE keying, rated at 4 A / 60 V, suitable for 5-core shielded or unshielded industrial cables.

Q: What cable diameter fits the PG11 cable gland?

A: The PG11 cable gland suits cable outer diameters of 7-9 mm. The clamp body provides reliable strain relief and sealing.

Q: What is the protection class and operating temperature range?

A: Protection class is IP67 (dust-tight and protected against temporary immersion). Operating temperature range is -25 to +85 .

Q: Does it support on-site manual wiring?

A: Yes. H1205M-11 is field-wirable with screw terminals, requiring no special crimping tools. Wiring and maintenance can be completed quickly on-site.

Q: How is mis-mating prevented?

A: The connector uses A-CODE keying with a 5-pin arrangement. Only matching male and female connectors can mate correctly, preventing equipment damage from mis-insertion.

Ordering Information

Item	Details
Ordering Model	H1205M-11
Product Name (CN)	M12
Product Name (EN)	M12 Male Field Wirable Assembly, Straight
Key Specifications	5-pin / A-CODE / PG11 / IP67

For bulk quotation, custom harness matching, or sample requests, please contact the sales team with detailed requirements.

(C) 2026 KRONZ Industrial Connectivity. Product parameters are subject to change without notice. Please refer to the actual delivery specification.



+8618924160375



sales02@kronz.cn



connector-industrial.com

Floor 7, Building 12B, Hanhe Robot Intelligent Manufacturing Base Exhibition Center, Xiangshan Avenue,
Zengcheng Economic Development Zone, Guangzhou, Guangdong Province, China