



M12 Female Field Wirable Connector with 12 Pin A-CODE Keying and IP67 Protection

Our Product Introduction

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: KRONZ
- Certification: CE
- Model Number: H1212FAV-0
- Minimum Order Quantity: 10 pieces
- Price: Negotiable
- Packaging Details: Paper box packing
- Delivery Time: 5-8 working days
- Payment Terms: D/P,T/T
- Supply Ability: 100000 pieces per month



Product Specification

- Standard: IEC 61076-2-101
- Pin Count: 12 Pin
- Coding: A-CODE
- Rated Current: 1.5 A
- Rated Voltage: 30 V
- Cable Outlet Diameter: 4-8 Mm
- Highlight: **12 Pin M12 Female Connector, A-CODE Keying Field Wirable Connector, IP67 Protection Angled Connector**

for more products please visit us on connector-industrial.com

Product Description

M12 Female Field Wirable Assembly, Angled

H1212FAV-0 is a field-wirable M12 female angled connector designed for industrial automation and fieldbus applications where space is limited, such as sensors, actuators, I/O modules, and control cabinet wiring.

The 90-degree angled outlet structure reduces cable bending radius and saves installation space compared with straight connectors. The 12-pin female interface with A-CODE keying effectively prevents mis-mating. Brass gold-plated contacts combined with screw clamp terminals allow reliable wiring on-site without special crimping tools, significantly reducing installation and maintenance costs.

The connector features a robust nickel-plated metal housing with a die-cast zinc clamp body, providing excellent EMI shielding and mechanical strength. Seals are made of FPM/FKM material, achieving IP67 protection and stable performance in dusty, oily, and briefly submerged environments. The product complies with IEC 61076-2-101 and supports more than 100 mating cycles, making it suitable for machine tools, robots, logistics conveyors, and new energy equipment.

Key Specifications

Parameter	Value
Ordering Model	H1212FAV-0
Type	Female / Angled (90°)
Pin Count	12 Pin
Coding	A-CODE
Connection method	Solder connection
Cable Gland	4-8 mm
Rated Current	1.5 A
Rated Voltage	30 V
Protection Class	IP67
Operating Temperature	-25 ~ +85

Technical Parameters

Parameter	Value
Standard	IEC 61076-2-101
Pin Count	12 Pin
Coding	A-CODE
Rated Current	1.5 A
Rated Voltage	30 V
Contact Resistance	≤ 5 mΩ
Insulation Resistance	≥ 100 MΩ
Connection method	Solder connection (Field Wirable)
Cable Outlet Diameter	4-8 mm
Protection Class	IP67

Operating Temperature	-25 ~ +85
Pollution Degree	3
Mechanical Life	>100 Mating Cycles
Housing Material	Nickel-plated Metal (Zinc Alloy Die-cast)
Coupling Nut Material	Zinc Alloy, Nickel-plated
Contact Material	Brass, Gold-plated
Insert Material	PA, Black
Clamp Body Material	Die-cast Zinc, Nickel-plated
Seal Material	FPM / FKM

Note: The above are typical parameters. Please evaluate the actual application in combination with cable specifications, installation method, and environmental conditions.

Product Features

- 12-pin high-density female interface with A-CODE keying prevents mis-mating and improves system safety.
- 90-degree angled metal housing saves routing space and reduces cable bend stress in compact enclosures.
- IP67 industrial protection blocks dust and water jets, suitable for outdoor, machine tool, and washdown environments.
- Field screw termination requires no crimping dies; a common screwdriver completes wiring for fast installation and maintenance.
- Metal housing and nickel-plated clamp body provide enhanced EMI shielding and mechanical durability.
- Gold-plated brass contacts deliver contact resistance as low as $\leq 5\text{ m}\Omega$, resisting oxidation and ensuring long-term stable conduction.
- Wide operating temperature range from -25 to +85 covers most industrial high/low temperature challenges.

Applications

H1212FAV-0 is suitable for a variety of industrial scenarios requiring reliable field connection of sensors and actuators to control systems, especially where space is constrained.

- Industrial Automation: PLC, I/O modules, sensors, and actuators field wiring in compact cabinets.
- Machine Vision & Inspection: Multi-core signal transmission for cameras and lighting controllers.
- Robotics & Conveyors: Resistant to vibration and oil, meeting mobile equipment connection requirements.



Frequently Asked Questions

Q: How many conductors does H1212FAV-0 support?

A: H1212FAV-0 is a 12-pin female angled field-wirable connector with A-CODE keying, rated at 1.5 A / 30 V, suitable for 12-core shielded or unshielded industrial cables.

Q: What cable diameter fits the cable gland?

A: The integrated cable gland suits cable outer diameters of 4-8 mm. The clamp body provides reliable strain relief and sealing.

Q: What is the protection class and operating temperature range?

A: Protection class is IP67 (dust-tight and protected against temporary immersion). Operating temperature range is -25 to +85 .

Q: Does it support on-site manual wiring?

A: Yes. H1212FAV-0 is field-wirable with screw terminals, requiring no special crimping tools. Wiring and maintenance can be completed quickly on-site.

Q: How is mis-mating prevented?

A: The connector uses A-CODE keying with a 12-pin arrangement. Only matching male and female connectors can mate correctly, preventing equipment damage from mis-insertion.

Ordering Information

Item	Details
Ordering Model	H1212FAV-0
Product Name (CN)	M12

Product Name (EN)	M12 Female Field Wirable Assembly, Angled
Key Specifications	12-pin / A-CODE / 4-8 mm / IP67 / Angled

For bulk quotation, custom harness matching, or sample requests, please contact the sales team with detailed requirements.

(C) 2026 KRONZ Industrial Connectivity. Product parameters are subject to change without notice. Please refer to the actual delivery specification.

KRONZ Kronz (guangzhou) Electronics Co., Ltd.

 +8618924160375  sales02@kronz.cn  connector-industrial.com

Floor 7, Building 12B, Hanhe Robot Intelligent Manufacturing Base Exhibition Center, Xiangshan Avenue,
Zengcheng Economic Development Zone, Guangzhou, Guangdong Province, China